

## **Cart Lift Folding Tables**

Cart Lift Fold Tables are customarily used as ergonomic solutions for delivering bulk goods to finishing stations. Clean, dry bulk items are loaded into custom designed wire baskets from a dryer or overhead rail system. The baskets are rolled into the folding table's self-locking forks and raised by the operator gradually to dump the goods on the table. The raising of the basket is controlled by a pushbutton on the front and back of the table. Lowering is only allowed from the rear corner pushbutton station where the operator can make sure there is nothing under the basket as it comes down. The hydraulic system allows the raising and lowering to be acomplished smoothly.



## Model CLFT Hydraulic Cart Lift Folding Tables

## **CLFT Standard Features**

- Rated Capacities
  - MODEL CLFT-250: 250 pound capacity 70" wide x 76" deep x 32.75" high 70" wide x 83.625" deep x 79.625" high with cart in place through tilt position
  - MODEL CLFT-550: 550 pound capacity 82" wide x 76" deep x 32.75" high 82" wide x 94" deep x 90" high with cart in place through tilt position
- Self contained hydraulic unit provides smooth lifting
- CLFT-250 and CLFT-550 have 1 HP 115V / 1 phase motor, 3 phase available
- Folding table surface is 66" (250) or 78" (550) wide x 32.5" deep
- Sides and table constructed of 11 Ga. powder coated mild steel
- Safety Features
  - Self locking forks secure cart while lifting
  - Formed steel sides and work table shield operator during lift action
  - Up only control at operator station to prevent lowering cart without seeing rear of lift
  - Up and down control located at load side for full view of cart while in motion
  - Side guards provided to cover pinch points
- Optional pneumatic CLFT available up to 1250 pound capacity

## **Cart Standard Features**

- 250 pound capacity cart
  - 37 cu. ft. capacity 61" long x 36" wide x 31" high 36.625" over-all
- 550 pound capacity cart
  - 55 cu. ft. capacity 71" long x 48" wide x 31" high 36.625" over-all
- Frame is contructed of 1" x 1" x 14 ga. painted mild steel tubing
- Sides and front constructed of painted mild steel wire mesh
- Solid bottom and back panel constructed of 14 ga. painted mild steel
- Heavy duty 4" swivel casters (with polyurethane tires)
- Built with locking channel bottom supports



A Member of the White Conveyors Family



5345 Truman Drive • Decatur, GA 30035 1-800-241-0990 • 1-770-981-5490 speedcheckconveyor.com